

FAX.

(800) 727-9957 (800) 727-9262

(213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com

TEL.



SPECIFICATION SHEET

PRODUCT #: CL-232-AB

Housing: Cast brass adjustable fixture, suspended inside a

reversible PVC sleeve with both flat and angle-cut

options on either end.

Fixture Specifications:

Finish: AB- Antique Bronze, Faceplate Natural toning

process. AB finish will vary due to artistic process.

Also available in SS finish.

Lens: Clear, tempered and heat resistant convex glass.

Extra flat lens included.

Socket: Top grade ceramic bi-pin socket with retention

clip.

Lamp: 12V, MR-16, 50W max.

> Available in LED (3.5W & 5W) or without lamp. See the Lamp Guide below for more information.

•Well Lights Cast Brass

Gasket: Silicone "0" ring seals faceplate to housing

providing weather tight protection.

Wiring: Fixture is prewired with a 3-ft 18-2 SJT-W direct

> burial cord. Wire connector sold seperately. Silicone filled direct buirial wire nut (CX-854) is

available from Corona Lighting.

Mounting: In-ground direct burial or concrete encasement.

Electrical Notes: A remote 12V transformer is required. Options are

available from Corona Lighting.


Voltage range for LED lamps are 9V-17V.

Some assembly needed. Proper grease/lubricant is suggested on threaded parts during installation.


Warranty: Limited lifetime warranty on brass fixture

against manufacturer's defects.





3.5W and 5W



AVAILABLE LED LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's defects	;)
--	----

		BEAM		COLOR &	RATED	HALOGEN
LAMP NUMBER	WATTS	SPREAD	LUMEN	TEMP.	HOURS	EQUIVALENT
L-ED16-3W-SP	3.5	15° Spot	270	2700K	50,000	25 Watt
L-ED16-3W-FL	3.5	45° Flood	270	2700K	50,000	25 Watt
L-ED16-3W-WF	3.5	60° Wide Flood	270	2700K	50,000	25 Watt
L-ED16-5W-SP	5	15° Spot	350	2700K	50,000	40 Watt
L-ED16-5W-FL	5	45° Flood	350	2700K	50,000	40 Watt
L-ED16-5W-WF	5	60° Wide Flood	350	2700K	50,000	40 Watt
L-ED16-COB5W-SP	5	15° Spot	450	2700K	50,000	50 Watt
L-ED16-COB5W-FL	5	38° Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-WF	5	60° Wide Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-SP3K	5	15° Spot	470	3000K	50,000	50 Watt
L-ED16-COB5W-FL3K	5	38° Flood	470	3000K	50,000	50 Watt
L-ED16-COB5W-WF3K	5	60° Wide Flood	470	3000K	50,000	50 Watt
■ Single color MR-16 LED available in AMBER, BLUE, GREEN, PURPLE, RED and VIOLET						

JOB INFORMATION

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

• When ordering LED lamp with a fixture your part number should follow the format below:

• CL - product # - lamp - wattage - lamp angle FL CL - 232-AB - L-ED16 - 5W -

Example: CL-232-AB-L-ED16-5W-FL

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.



ACCESSORIES SHEET

1633 Staunton Ave Los Angeles, CA 90021

TEL. FAX. (800) 727-9262 (800) 727-9957

(213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

PRODUCT #: CL-232-AB

• Well Lights

• Cast Brass


Cable Connector

CX-854 Direct Burial Silicone Filled Wire Nut, Tan



Faceplates

CX-880B-AB Brass Louvered Coverplate



Special Lenses & Honeycomb Louvers

CX-238	MR-16 Snap-on holder, Silver Plated
CX-239	MR-16 honeycomb louver, Black
CX-240-AM	MR-16 color lens, Amber
CX-240-BL	MR-16 color lens, Blue
CX-240-GR	MR-16 color lens, Green
CX-240-RD	MR-16 color lens, Red
CX-240-YL	MR-16 color lens, Yellow
CX-241	MR-16 lens, Linear Spread
CX-242	MR-16 lens, Frosted
CX-243	MR-16 lens, Prismatic

For MR-16 Lenses and Louvers, you will need the CX-238

