

SPECIFICATION SHEET

 1633 Staunton Ave

 Los Angeles, CA
 90021

 TEL.
 FAX.

 (800) 727-9262
 (800) 727-9957

 (213) 747-4500
 (213) 747-3234

E-Mail: sales@coronalighting.com

PRODU	ICT # : CL-298-BZ-27K	•Rail Lights	• Aluminum
Fixture Specifications:			
Light Bar Housing:	 Die-Cast Aluminum. Replaceable LED Capsule. Fully Potted. 	Wiring:	Fixture is prewired with a 10-ft 18-2 direct burial cord,pre-stripped for easy connection, wire connector sold seperately.
Finish:	BZ- Bronze.		Universal connector (CX-839), silicone filled wire nut
Lighting Source:	Integrated LED Strip (12 Chips), Wattage: 2W, beam. Spread: 120 Degree, Light Output: 100 Lumens, Color Temperature: 2700K Warm White (3000K Cool White also available). Operating Voltage: 9-17V AC. CRI: RA >85. Halogen Equivalent: 20W. Ambient Operating Temperature: -4° F - 122° F	Mouting Brackets:	(CX-854) or quick locking wire connector (CX-LOC) are available from Corona Lighting. Stainless Steel Mounting Bracket is removable for further applications. Break off corners for easy installa- tion. Additional shorter Mounting Brackets (Small and "L" Shape) provided. Supplied with Wall Anchors and Screws.
Features:	IP65. Suitable for Damp Locations. Rated for Outdoor. Dimmable with magnetic transformers.	Electrical Notes:	A remote 12V magnetic transformer is required, can be be ordered from Corona Lighting, seperately. Not for
Dimensions: 7" X ⁷ / ₈ "		use with electronic transformer. Increasing voltage above 12 volts AC may decrease life of LED chips.	
Warranty:	10 year warranty, with a rated life of 50,000 hours.	Applications:	Retaining walls, Patios, Gazebos, Decks, Benches, Stairs, and Outdoors Living Spaces.
10' wire cord 10' Wi			
Replaceable LED Capsule			
	is attached to the housing with two S.S. screws, maki		JOB INFORMATION
and install.			TYPE: DATE:
			JOB NAME & ADDRESS:
Housing			PRODUCT #:
			TOTAL QUANTITY:
		LAMP TYPE & WATTAGE:	
			TRANSFORMER:
			CONTRACTOR:
(novable Capsule	SPECIFIER:

