

SPECIFICATION SHEET

1633 Staunton Ave Los Angeles, CA 90021

TEL. FAX.

(800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

PRODUCT #: CL-353

100001 # . OL-333

Housing: Diecast aluminum

Fixture Specifications:

Finish: Polyester UV powder coated available in, BK- Black

BZ- Bronze, WH- White.

Lens: Frosted, tempered and heat resistant glass lens.

Socket: Top grade fixed T5 wedge socket

Lamp: BK&WH- 12V T3, 35W max.

Available with no lamp or in LED (2W or 2.5W). See the Lamp Guide below for more information.

BZ- 12V T5, 18W max.

Available in 1.5W LED or without lamp.

See the Lamp Guide below for more information.

Step Light

• Aluminum

Wiring: Fixture prewired with a 3ft direct burial cord. Wire

connector sold seperately. Silicone filled wire nut

(CX-854) are available from Corona Lighting.

Mounting: Surface mounted, mounting plate is included.

Outdoor use only.

Gasket: Silicone "O" ring seals faceplate to housing providing

weather tight protection.

Electrical Notes: A remote 12V transformer is required. Options are

available from Corona Lighting.

Voltage ranges for LED lamps is 11-12.5V(BZ) and


8-21V (BK/WH).

Warranty: One year warranty providing protection against

manufacturer's defects.



WH- White finish is shown





Į	AVAILABLE LED LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's	defects)
ļ		

FOR BZ		BEAM		COLOR &	RATED	HALOGEN
LAMP NUMBER	WATTS	SPREAD	LUMEN	TEMP.	HOURS	EQUIVALENT
L-EDT5-1.5W	1.5	180°	120	2700K	12,000	10 Watt

FOR BK & WH

			COLOR &	RATED	HALOGEN
WATTS	SPREAD	LUMEN	TEMP.	HOURS	EQUIVALENT
2	360°	200	2700K	25,000	20 Watt
2.5	180°	240	2700K	25,000	35 Watt
2	360°	210	3000K	25,000	20 Watt
2.5	180°	250	3000K	25,000	35 Watt
2	360°	170	2000K	25,000	20 Watt
	2 2.5 2	2 360° 2.5 180° 2 360° 2.5 180°	2 360° 200 2.5 180° 240 2 360° 210 2.5 180° 250	WATTS SPREAD LUMEN TEMP. 2 360° 200 2700K 2.5 180° 240 2700K 2 360° 210 3000K 2.5 180° 250 3000K	WATTS SPREAD LUMEN TEMP. HOURS 2 360° 200 2700K 25,000 2.5 180° 240 2700K 25,000 2 360° 210 3000K 25,000 2.5 180° 250 3000K 25,000

* AM- Amber color

For more additional Lamps, and accessories visit Coronalighting.com

JOB INFORMATION

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

[•] If you are ordering LED lamps you should follow the format below:



Example: CL-353-BK-L-EDT5-1.5W



ACCESSORIES SHEET

1633 Staunton Ave Los Angeles, CA 90021

TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

PRODUCT #: CL-353

Step Light

Aluminum

Cable Connector

CX-854 Direct Burial Silicone Filled Wire Nut, Tan

