

ARCHITECTURAL GRADE SERIES

SPECIFICATION SHEET

1633 Staunton Ave Los Angeles, CA 90021

TEL. FAX.

(800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

PRODUCT #: CL-362B-SI

OT II . OL GOLD OI

• Step Light

Wiring:

• Steel & Brass

Fixture Specifications:

Housing: White powder coated steel mount box with

S.C. Bayonet Socket

Faceplate: Stamped brass available in SI- Silver Plated.

Also in:

Aluminum: BK-Black, BZ-Bronze, RT- Rust or

WH-White

Stamped Metal: **AB**- Antique Bronze, **GM**-Gun Metal, **OC**- Old Copper, **RC**- Raw Copper

Lens: High impact white polycarbonate lens

Lens is secured and sealed to faceplate.

Socket: Top grade, fixed S.C. Bayonet socket.

Lamp: 12V, S.C. Bayonet, 18W max.

Available in LED (2W & 2.5W) or without lamp. See the Lamp Guide below for more information.

Gasket: Silicone gasket providing water-tight protection.

Fixture comes prewired with a 12 inch direct burial

cord. Wire connector sold seperately.

Silicone filled wire nut (CX-854) are available from

Corona Lighting.

Mounting: Recessed box to mount into concrete, brick or

masonry. Outdoor use only.

Electrical Notes: A remote 12V transformer is required. Options are

available from Corona Lighting.

Voltage range for LED lamps are 8V-21V.

Warranty: AB, GM, OC, SI, and RC- Limited lifetime warranty


on fixture housing and faceplate against

manufacturer's defects.

BK, **BZ**, **RT** and **WH**- Five year warranty on fixture housing and faceplate against manufacturer's

defects.







AVAILABLE LED LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's defects)

_	DEAW		_ COLOR &	KAIED	HALOGEN
WATTS	SPREAD	LUMEN	TEMP.	HOURS	EQUIVALENT
2	360°	200	2700K	25,000	20 Watt
2.5	180°	240	2700K	25,000	35 Watt
2	360°	210	3000K	25,000	20 Watt
2.5	180°	250	3000K	25,000	35 Watt
2	360°	170	2000K	25,000	20 Watt
	2 2.5 2	WATTS SPREAD 2 360° 2.5 180° 2 360° 2.5 180°	WATTS SPREAD LUMEN 2 360° 200 2.5 180° 240 2 360° 210 2.5 180° 250	WATTS SPREAD LUMEN TEMP. 2 360° 200 2700K 2.5 180° 240 2700K 2 360° 210 3000K 2.5 180° 250 3000K	WATTS SPREAD LUMEN TEMP. HOURS 2 360° 200 2700K 25,000 2.5 180° 240 2700K 25,000 2 360° 210 3000K 25,000 2.5 180° 250 3000K 25,000

*AM- Amber color

For more additional Lamps, and accessories visit Coronalighting.com

IOR.	INFO	RM	ΔΤΙΟ	NC

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

• CL - product # - color - lamp - wattage

CL - 362B - SI - L-EDBA - 2W-3K

Example: CL-362B-SI-L-EDBA-2W-3K

[•] If you are ordering LED lamps you should follow the format below:



ARCHITECTURAL GRADE SERIES

ACCESSORIES SHEET

1633 Staunton Ave Los Angeles, CA 90021

FAX. (800) 727-9957 (800) 727-9262 (213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com

• Steel & Brass

PRODUCT #: CL-362B-SI


Step Light

Faceplates

CX-874B-SI Brass, eyelid faceplate with white acrylic lens


Stamped brass available in .SI- Silver Plated Also available in:

Aluminum: BK-Black, BZ-Bronze, RT- Rust or WH-White Stamped Metal: AB- Antique Bronze, GM-Gun Metal, OC-Old Copper, RC- Raw Copper



Mount Box

CX-731 Steel Mount Box, No Lamp



Lamp not included. Shown for demonstration.

Cable Connector

Direct Burial Silicone Filled Wire Nut, Tan CX-854

